



## KDP & KDPR SITE INSPECTION SURVEY

Please Note: Floor must be close to level where unit is being installed.

Site Name: \_\_\_\_\_

Contact Name: \_\_\_\_\_

Contact Phone/Email: \_\_\_\_\_

Dealer Name: \_\_\_\_\_

Point of Contact: \_\_\_\_\_

Rep Group: \_\_\_\_\_

Contact Phone: \_\_\_\_\_

Rep Contact: \_\_\_\_\_

Contact Email: \_\_\_\_\_

**Electrical:** Please check the appropriate box  
Electrical Connections Located on Top Left Side of proofer.

### KDP

	Model	Volts	Phase	Amps	kW	Hertz
<input type="checkbox"/>	KDP11	208	1	24	5	60
<input type="checkbox"/>	KDP11	240	1	21	5	60
<input type="checkbox"/>	KDP12	208	1	24	5	60
<input type="checkbox"/>	KDP12	240	1	21	5	60
<input type="checkbox"/>	KDP13	208	1	48	10	60
<input type="checkbox"/>	KDP13	240	1	42	10	60
<input type="checkbox"/>	KDP21	208	1	24	5	60
<input type="checkbox"/>	KDP21	240	1	21	5	60
<input type="checkbox"/>	KDP22	208	1	48	10	60
<input type="checkbox"/>	KDP22	240	1	42	10	60
<input type="checkbox"/>	KDP23	208	1	72	15	60
<input type="checkbox"/>	KDP23	240	1	63	15	60
<input type="checkbox"/>	KDP23	208	3	42	15	60
<input type="checkbox"/>	KDP23	240	3	36	15	60
<input type="checkbox"/>	KDP31	208	1	48	10	60
<input type="checkbox"/>	KDP31	240	1	42	10	60
<input type="checkbox"/>	KDP32	208	1	72	15	60
<input type="checkbox"/>	KDP32	240	1	63	15	60
<input type="checkbox"/>	KDP32	208	3	42	15	60
<input type="checkbox"/>	KDP32	240	3	36	15	60
<input type="checkbox"/>	KDP33	208	1	72	15	60
<input type="checkbox"/>	KDP33	240	1	63	15	60
<input type="checkbox"/>	KDP33	208	3	42	15	60
<input type="checkbox"/>	KDP33	240	3	36	15	60

## **KDPR**

	<b>Model</b>	<b>Volts</b>	<b>Phase</b>	<b>Amps</b>	<b>kW</b>	<b>Hertz</b>
<input type="checkbox"/>	KDPR11	208	1	24	5	60
<input type="checkbox"/>	KDPR11	240	1	21	5	60
<input type="checkbox"/>	KDPR12	208	1	24	5	60
<input type="checkbox"/>	KDPR12	240	1	21	5	60
<input type="checkbox"/>	KDPR13	208	1	48	10	60
<input type="checkbox"/>	KDPR13	240	1	42	10	60
<input type="checkbox"/>	KDPR21	208	1	24	5	60
<input type="checkbox"/>	KDPR21	240	1	21	5	60
<input type="checkbox"/>	KDPR22	208	1	48	10	60
<input type="checkbox"/>	KDPR22	240	1	42	10	60
<input type="checkbox"/>	KDPR23	208	1	72	15	60
<input type="checkbox"/>	KDPR23	240	1	63	15	60
<input type="checkbox"/>	KDPR23	208	3	42	15	60
<input type="checkbox"/>	KDPR23	240	3	36	15	60
<input type="checkbox"/>	KDPR31	208	1	48	10	60
<input type="checkbox"/>	KDPR31	240	1	42	10	60
<input type="checkbox"/>	KDPR32	208	1	72	15	60
<input type="checkbox"/>	KDPR32	240	1	63	15	60
<input type="checkbox"/>	KDPR32	208	3	42	15	60
<input type="checkbox"/>	KDPR32	240	3	36	15	60
<input type="checkbox"/>	KDPR33	208	1	72	15	60
<input type="checkbox"/>	KDPR33	240	1	63	15	60
<input type="checkbox"/>	KDPR33	208	3	42	15	60
<input type="checkbox"/>	KDPR33	240	3	36	15	60

## **Shipping Style:**

<b>Model</b>	<b>Description</b>	<b>Weight (lbs.)</b>	<b>Dimension L x W x H</b>	<b>Shipping Class</b>	<b>NMFC #</b>
<b>KDP11</b>	SKID 1 - walls & misc.	860	96 x 48 x 48	85	114340-3
<b>KDPR11</b>	SKID 1 - walls & misc.	860	96 x 48 x 48	85	114340-3
	SKID 2 - refrigeration module	230	34 x 40 x 37	85	114340-3
<b>KDP21</b>	SKID 1 - walls & misc.	1,315	96 x 48 x 42	85	114340-3
<b>KDPR21</b>	SKID 1 - walls & misc.	1,315	96 x 48 x 42	85	114340-3
	SKID 2 - refrigeration module	230	34 x 40 x 37	85	114340-3

## **Minimum Clearances:**

1" (25mm) Sides, 19" (484mm) Top, 3" (76mm) Rear

**Check this box to verify you have the minimum clearances available.**

**Note:** 10' ceiling height required for proper airflow and service access. 1" clearance between proofer and oven recommended to ensure proper proofer operation.

## **Drain Connection Size:**

½" diameter (Applies to the KDPR only. Unit can only be drained from the back).

**Check this box to verify you have the correct drain connection size available.**

**Note:** Drain not included.

## **Water Requirements and Filters**

Every water source is different and needs to be tested by a water quality professional. For any proofer that connects to a water source, the use of good quality feed water is the responsibility of the Owner/User. **The use of poor-quality feed water will void equipment warranties. Water filter recommended Doyon part #50-1530.**

### **Water Quality Requirements to Meet Warranty Standards.**

Total Dissolved Solids (TDS)	Less than 100 parts per million
Total Alkalinity	Less than 120 parts per million
Silica	Less than 13 parts per million
Sulfates	Less than 40 parts per million
Chlorides	Less than 30 parts per million
Chlorine/Chloramines	0 parts per million
pH	Between 7.0 – 8.0

Water line requirements: 1/4" TUBE Cold Water Line Connection Required with 15-25 PSI.

**Check this box to verify you have the correct water line.**

## **Floor Requirements:**

The Unit should be installed on level surface within 1/8" per foot for proper installation. Slope should not exceed 3/4" in all directions under the unit. Unit must be installed on a non-combustible material floor with a cleanable surface.

**Check this box if the floor meets the requirements.**

## **Delivery:**

Proofer will be delivered to site. The site has the equipment and tools to remove the proofer from the truck.

Proofer will be delivered to the dealer. The dealer has the equipment and tools to remove the proofer from the truck. Dealer will coordinate the delivery to site at least 24hrs before installation date.

**Note:** Lead time for installation is 3-4 weeks. Keep in mind that installation cannot be arranged on the same day as delivery.