Refrigerator/Freezer Thermometers

	2560	25HP-01	330	335-01	535-01	PM180
Temperature Range:	-22° to 122°F (-30° to 50°C)	-20° to 80°F (-29° to 27°C)	-40° to 120°F (-40° to 50°C)	-40° to 80°F (-40° to 25°C)	-20° to 120°F (-30° to 50°C)	-25° to 180°F (-32° to 82°C)
Accuracy:	±1°F (0.5°C)	±2°F (±1°C)	±2°F (±1°C)	±2°F (±1°C)	±5°F (±2°C)	±2°F (±1°C)
Housing Material:	Antimicrobial Plastic	Stainless Steel	Food Grade Plastic	Stainless Steel	Plastic	Plastic
Dimensions:	3.562" x 1.25" x 3.5" (90 mm x 32 mm x 89 mm)	2.375" x 1.5" x 3" (60 mm x 38 mm x 76 mm	0.625" x 0.25" x 4.25" (16 mm x 6.4 mm x 108 mm)	4.75" x 0.875" x 1.125" (121 mm x 22 mm x 29 mm)	2" (51 mm)	5" x 3.75" x 0.875" (127 mm x 95 mm x 22 mm)
Lens Material:	Food Grade Polycarbonate	Glass	-	Food Grade Polycarbonate	Plastic	-
Weight:	1.5 oz (43 g)	1.5 oz (43 g)	0.25 oz (7 g)	1 oz (28 g)	0.5 oz (14 g)	5 oz (142 g)
Regulatory Listings:	CE (NSF) RoHS	(NSF.)	NSF _s)	(NSF,)	-	C€ TROHS
Warranty:	Lifetime	1 Year	1 Year	1 Year	1 Year	1 Year







The 2560 is a low temperature digital thermometer designed to hang or stand within the food zone inside cold storage cabinets. Cable-ties included for added mounting security.

PM180 Dual-Cool™ Panel Thermometer



The Dual-Cool is Cooper-Atkins' first dual-temperature panel thermometer with interchangeable probes, Min/Max alarm settings and Hi/Lo temperature recall. Equipped with user-adjustable settings, it can simultaneously measure temperatures within two separate storage environments or two locations inside of the same reach-in, walk-in or hot-holding cabinet.

PM180-01

- PM180 Panel Thermometer
- 2013 Air Probe
- 2113 Solid Simulator Probe

PM180-02

- PM180 Panel Thermometer
- (2) 2013 Air Probes

PM180-03

- PM180 Panel Thermometer
- (2) 2113 Solid Simulator Probes