Storage, Wall and Panel Thermometers

Get accurate internal temperature readings without opening any doors. Cooper-Atkins' panel meters are the perfect choice for use in walk-in refrigerators, tanks, refrigerated display cases, holding cabinets, dairy cases, and more. Save time and lower energy costs by monitoring cold storage temperatures from the outside.

	250-0-1	25506	255-14	268	6142-20	SP160-0 / 01 Black / White	PM120	T158
Temperature Range:	40° to 120°F (-40° to 50°C)	-60° to 120°F (-50° to 50°C)	10° to 80°F	40° to 120°F (-40° to 50°C)	-40° to 60°F (-40° to 15°C)	-58° to 158°F (-50° to 70°C)	-40° to 122°F (-40° to 50°C)	(Internal): 32° to 122°F (0° to 50°C (External): -58° to 158°F (-50° to 70°C)
Accuracy:	±2°F (±1°C)	±2°F (±1°C)	±2°F	±2°F (±1°C)	±2°F (±1°C)	±2°F (±1°C)	±1.8F° (±1C°)	±2°F (±1°)
Housing Material:	Plastic	Plastic	Plastic	Plastic	Stainless Steel	Plastic	Plastic	Plastic
Lens Dimensions:	4.5" (114 mm)	3.75" (95 mm)	3.75" (95 mm)	-	2" (51 mm)	-	-	-
Lens Mate- rial:	Clear Acrylic	Clear Acrylic	Clear Acrylic	-	Polycarbonate	-	-	-
Power:	-	-	-	-	-	Solar with battery backup 1.5v (AAA)	1.5v (AA)	1.5v (AAA)
Weight:	4 oz (113 g)	3 oz (85 g)	3 oz (85 g)	2 oz (57 g)	5 oz (142 g)	3 oz (85 g)	2 oz (57 g)	5.5 oz (156 g)
Regulatory Listings:	-	-	-	-	(NSF.)	CE RoHS	CE RoHS	C€ 🗵 RoHS
Warranty:	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year









268
Glass stick Indoor/Outdoor
Thermometer with Suction Cups



PM120 Mini Rectangular Panel Thermometer



