

HIGH FLOW CSR OUAD-4FC SYSTEM

DELIVERS PREMIUM QUALITY WATER FOR HIGH FLOW COMBINATION APPLICATIONS

High Flow CSR Quad - 4FC System: EV9329-44 4FC Replacement Cartridges: EV9692-21 (1 PK) EC110 Replacement Cartridge: EV9534-12 (12 PK) SS-XL ScaleStick Cartridge: EV9799-42 (6 PK)



APPLICATIONS

- Multiple Equipment and Combination ◆ High-Volume Installations **Applications**

FEATURES • BENEFITS

- Provides premium quality water to high flow fountain, coffee and ice machines
- Sanitary cartridge replacement is simple, quick and clean; internal filter parts are never exposed to handling or contamination
- Extended-life 4FC Cartridges feature balanced chemical and mechanical reduction for optimum performance in varying water qualities
- Exclusive Pentair§ Everpure§ Fibredyne™ II submicron carbon block technology provides superior chlorine taste & odor reduction and micro-filters dirt and particles as small as 0.5 micron in size by mechanical means

- Proprietary Pentair Everpure Fibredyne II filtration media effectively inhibits the growth of bacteria on the filter media that decreases product life
- Allows for optimal flow rate and contaminant reduction capacity in tight spaces
- Reduces chlorine taste & odor and other offensive contaminants that can adversely affect the taste of beverages
- Compact design, with 10" prefilter Pentair Everpure SR-X Feeder with Pentair Everpure SS-XL ScaleStick§ cartridge inhibits scale buildup in ice machines and coffee brewers
- NSF/ANSI Standard 53 certified to reduce cysts such as Cryptosporidium and Giardia by mechanical means

INSTALLATION TIPS

- Choose a mounting location capable of safely supporting the full weight of the system when in operation.
- Use 3/4" water line.
- Fountain equipment connections are made to the outlet part of the system before the SR-X System.
- Coffee brewer and ice machine connections are made after the SR-X Feeder; a tee is
- Install vertically with cartridges hanging down and allow 2 1/2" (6.35 cm) clearance below the cartridge for easy replacement.
- Flush cartridges by running water through flushing valve for five (5) minutes at full flow.

OPERATION TIPS

- Change filter cartridges on a regular six (6) month preventative maintenance program.
- Change cartridges when capacity is reached or when pressure falls below 10 psi (0.7 bar).
- Change SS-XL Cartridge before Hydroblend§ compound is completely used up.
- Change Pentair Everpure EC110 Prefilter Cartridge when excessively dirty.
- Always flush the filter cartridge at time of installation and cartridge change.


SIZING

- Service Flow Rate: Maximum 10.0 gpm (37.85 Lpm)
- Rated Capacity: 60,000 gallons (227,124 L)

HIGH FLOW CSR QUAD-4FC SYSTEM

FV9329-44

High Flow CSR Quad – 4FC System: EV9329-44 4FC Replacement Cartridges: EV9692-21 (1 PK) EC110 Replacement Cartridge: EV9534-12 (12 PK) SS-XL ScaleStick Cartridge: EV9799-42 (6 PK)



SPECIFICATIONS

- Service Flow Rate
 Maximum 10.0 gpm (37.85 Lpm)
- Rated Capacity
 60,000 gallons (227,125 L)
- Pressure Requirements
 10 125 psi (0.7 8.6 bar), non-shock
- Maximum Temperature 35 100°F(2 38°C)
- Overall Dimensions
 19.5" H x 34" W x 6.75" D
 (49.53 cm x 86.4 cm x 17.1 cm)
- Inlet Connection 3/4"
- Outlet Connection 3/4"

- Electrical Connection
 None required
- Shipping Weight 37 lbs (16.78 kgs)
- Operating Weight 45 lbs (20.41 kgs)



System Tested and Certified by NSF International against NSF/ ANSI Standards 42 and 53 for the reduction of:

STANDARD NO. 42 — AESTHETIC EFFECTS Chemical Reduction Taste & Odor STANDARD NO. 53 -HEALTH EFFECTS Mechanical Filtration

Mechanical Filtration Nominal Particulate Class I

EPA Est. No. 002623-IL-002

Cyst



WARRANTY

Everpure water treatment systems by Pentair (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Pentair will provide a copy of the warranty upon request.

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

Since the conditions under which our products may be used are beyond our control, we cannot accept any liability with respect to the improper installation, application and/or use of our products.



World Headquarters 1040 Muirfield Drive Hanover Park, IL 60133 United States 800.942.1153 (US Only) 630.307.3000 Main cseverpure@pentair.com

Europe
Pentair Water Belgium BVBA
Industriepark Wolfstee,
Toekomstlaan 30,
B-2200 Herentals
Belgium
+32.(0).14.283.504 Tel
sales@everpure-europe.com

Australia 1-21 Monash Drive Dandenong South, Vic 3175 Australia 011.1300 576 190 Tel au.everpure@pentair.com

Japan Inc.
Hashimoto MN Bldg. 7F,
3-25-1 Hashimoto, Midori-ku,
Sagamihara-shi
Kanagawa 252-0143
Japan
81.(0)42.775.3011 Tel
info@everpure.co.jp

China 21F Cloud 9 Plaza, NO 1118 Shanghai, 200052 China 86.21.3211.4588 Tel china.water@pentair.com

Southeast Asia 390 Havelock Road, #04-01 King's Centre Singapore 169662 65.6768.5800 Tel cseverpure@pentair.com India Boulevard, B-9/A, 7th Floor - Tower B Sector 62 Noida - 201301 91.120.419.9444 Tel indiacustomer@pentair.com

§ Pentair trademarks and logos are owned by Pentair plc or its affiliates. For a detailed list of where Pentair trademarks are registered, please visit www.pentair.com/en/registrations.html. Third party registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.