

Camshelving® Elements XTRA Series

Mobile Drying and Storage Racks 3 Shelves – Vertical

	HEIGHT	DEPTH	LENGTHS
	1	1	2
_	78¼"	24"	48" 60"

4 Shelves - Angled

HEIGHT	DEPTH	LENGTH
1	1	1
78¼"	24"	48"

• Vertical Drying and Storage Rack includes:

2 factory assembled mobile post kits, 6 shelf traverses, traverse dovetails, 12 or 15 vertical drying cradles and 4 premium swivel casters with total locking brake. 48" long - ships 5 cartons. 60" long - ships in 6 cartons.

• Angled Drying and Storage Rack includes:

2 factory assembled mobile post kits, 8 shelf traverses, traverse dovetails, 16 angled drying cradles and 4 premium swivel casters with total locking brake. Ships in 5 cartons.



Project ______
Item No.

Model No. _____

Vertical Drying and Storage Rack

Quantity __

Angled Drying and Storage Rack



Features & Benefits

- Use in walk-in coolers, freezers, dry storage, warewashing areas, loading docks or front of the house. Withstands storage temperatures -36° to 190°F (-38° to 88°C). Impervious to moisture, chemicals, salt, food acids and humidity.
- Posts and traverses are made of a revolutionary, extremely strong composite material with a smooth, easy to clean surface. Stronger than common wire shelving and lighter in weight than Camshelving Premium Series. Traverse dovetails are separate from the posts and attach easily to secure the shelf traverses.
- Premium caster is made of highly durable, non-corrosive plastic with a 5" (12,7 cm) swivel, non-marking thermoplastic rubber wheel. Total locking brake locks both swivel motion and the wheel.
- Optional donut bumper offers added protection during transport and when maneuvering mobile units into place against walls or alongside other units for storage.
- Posts and traverses wipe clean. Traverses and shelf plates remove easily for cleaning.
- Shelf traverses can be removed and adjusted at 4" (10,2 cm) increments.
- Requires some assembly with minimal parts.
 Use a rubber mallet only.
- Lifetime warranty against rust and corrosion (posts, traverses and shelf plates).
- Available in 1 color Speckled Gray (480).

WEIGHT BEARING CAPACITY

Weight must be evenly distributed across the entire shelf.

WOBILE UNITUnit only*Unit length 24-60"750 lbs.

Approvals



Post Connectors, Corner Connectors, Floor Fastener, Wall Fastener, Identification Tags, Shelf Rails, Single Shelf Security Cage, Peg Board and Shelf Divider Bars are not NSF listed.



^{*} Due to the weight bearing capacity of casters, maximum weight load on an entire Mobile Unit is 750 lbs.

Camshelving® Elements XTRA Series

Mobile Drying and Storage Racks

3 Shelves - Vertical

4 Shelves - Angled

Project _	
Itam Na	
ILGIII NU	
Model No.	

781/4"

Vertical Drying and Storage Rack

24"

CODE	DIMENSIONS D x L x H	HOLDING CAPACITY		
EXMU244878DRPKG	24" x 48" x 781/4"	84 Trays		
EXMU246078DRPKG	24" x 60" x 781/4"	105 Trays		
Color: Speckled Gray (480).				



Angled Drying and Storage Rack

24"
DEPTH

CODE	DIMENSIONS D x L x H	HOLDING CAPACITY		
EXMU244878PDPKG	24" x 48" x 781/4"	128 Pellets and Bases		
		or 16 GN 1/1 Food Pans		
Color: Speckled Gray (480).				



*Includes 5" casters.

Optional Accessories

- ☐ Donut Bumper
- ☐ Shelf Identification Tags
- □ Shelf Rails
- □ Peg Board

Architect Specs

thermoplastic rubber wheel.

Posts and Traverses: Proprietary non-corrosive composite material.
Post Connectors: Reinforced polypropylene.
Post Connector Collar Wedges: Reinforced nylon.
Traverse Dovetails: Reinforced nylon.
Drying Cradles: High impact ABS material.
Caster: Non-corrosive plastic body and brake with non-marking

Approvals



Post Connectors, Corner Connectors, Floor Fastener, Wall Fastener, Identification Tags, Shelf Rails, Single Shelf Security Cage, Peg Board and Shelf Divider Bars are not NSF listed.



Printed in USA. 04/24