

COMMERCIAL

#### Refrigeration Equipment Slide Top Bottle Cooler 95 " Long

738293 (KCHBC95)	Slide Top Bottle Cooler 95 " Long

## **Short Form Specification**

#### ltem No.

95" wide Bottle Cooler with 3 sliding tops. Exterior back and side panels in painted steel, exterior bottom panel in galvanized steel, top panel in 304 stainless steel; interior side panels in 430 stainless steel, interior back panel, interior bottom panel and worktop in 304 stainless steel. Fin & tube condenser to improve the performances in high temperature environments. Automatic Defrost Cooling System and electronic temperature control.

Vinyl-coated steel adjustable dividers and locking lids.

R290 gas in refrigeration circuit. ETL Safety and Sanitation certified. 3/5 Years warranty.

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	

# **Main Features**

- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Vinyl-Coated Steel adjustable dividers to customize bottle storage effortlessly.
- Locking doors.
- External temperature display.
- Cabinet completely insulated with high density polyurethane for low environmental impact.
- Locking lids.

# Construction

- Pre-wired heavy duty power cord.
- Electronic control to select temperatures.

# **Sustainability**

- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) CFC and HCFC free.

APPROVAL:

Part of

Kelvinator Commercial www.kelvinatorcommercial.com



### Refrigeration Equipment Slide Top Bottle Cooler 95 " Long

115 V/1 ph/60 Hz

USA NEMA 5-15P

95 5/16" (2421 mm)

28 9/16" (725 mm)

34 15/16" (888 mm)

26 1/16" / (662 mm)

22 15/16" / (583 mm)

60 3/8" / (1534 mm)

39 3/4" (1010 mm)

64.92 ft<sup>3</sup> (1.84 m<sup>3</sup>)

Black Prepainted Steel

ETL C&US;ETL SANITATION

381 lbs (173 kg)

3 - 513x605

Stainless Steel

3 / 5 years

1/5 hp

32 °F

41 °F

Fin & tube

3 Amps

R290

3 100 g

Auto Defrost

0.31 kW

29.1 cu.feet

3

**Electric** 

Plug type:

Supply voltage: 738293 (KCHBC95)

Capacity: Gross capacity:

**Electrical power, max:** 

**Key Information:** 

External dimensions, Width:

External dimensions, Depth:

External dimensions, Height:

Internal Dimensions (depth):

Internal Dimensions (height):

Internal Dimensions (width):

Number and type of grids

Type of external material:

Type of internal material:

**Compressor power:** 

Condenser type:

**Refrigerant type:** 

**Refrigerant weight:** 

**GWP Index:** 

Sustainability Current consumption:

Defrost type:

**Refrigeration Data** 

Operating temperature min.:

**Operating temperature max.:** 

Shipping height:

Shipping weight:

Shipping volume:

(included):

Warranty:

Approvals

Number and type of doors:

# Front 2421~ 1.4"-290mm -844.5mm 35"-888mm 53.2"-14<u>.6"-371mm</u> Side 28.5"-725mm 27"-687mm <u>– 322m</u>m ₩ 26.1"-663mm **EI** = Electrical connection Top 1"-283m 30.1"-764mm 30 1"-764mm 30.1"-764mm



Refrigeration Equipment Slide Top Bottle Cooler 95" Long

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Kelvinator Commercial is a pending or registered trademark of Electrolux Consumer Products, Inc., and is used under a license from Electrolux Consumer Products, Inc.