



24" ADA-HEIGHT COMPLIANT REFRIGERATOR
Single Door



JOB	
AREA	
ITEM NO.	
MODEL NO.	



HB24RS-BS-STK

MODEL NO.
HB24RS-BS-STK

Note: NSF/ANSI Standard 7 Listed for the storage and display of bottled or canned products only.

KEY PRODUCT FEATURES AND BENEFITS

- ADA-height compliant controls and height designed to fit under ADA-height compliant counter tops
- All stainless steel interior ensures consistent cabinet temperature and hygienic easy to clean environment that will not absorb odors over time
- Full extension, smooth glide shelving gives easy access to product and faster, more ergonomic product loading
- Ultra-quiet and energy efficient smart compressor – compressor ramps up as additional cooling is needed maximizing energy savings while decreasing pull down time
- NSF rated digital controller allows for precision temperature setting and features an audible door alarm, alerting the operator if an intrusion will not allow the door to close
- Open shelf design allows cold air to surround product reducing temperature variation in the cabinet and extending product life
- 525 BTU/hr fast pull down of product to serving temperature

Quick Features:

- 2" foamed-in-place eco-friendly insulation provides energy savings with zero ozone depletion
- Smart defrost cycle runs only when needed, increasing energy efficiency over standard systems
- Selectable white or blue LEDs provide crisp line of sight to product
- Field reversible door allows for easy replacement or re-purposing
- Door lock optional
- NSF 7 rated for canned and bottle beverage storage
- No plumbing required
- 1 Year Warranty, 5 Year Compressor Warranty



24" ADA-HEIGHT COMPLIANT REFRIGERATOR
Single Door

MODEL NUMBERS		HB24RS-BS-STK
MODEL DESCRIPTION		Refrigerator
OVERALL DIMENSIONS	Width - in. (mm)	23-7/8 (606)
	Depth - in. (mm)	24 (610)
	Height - in. (mm)	32 (813)
STANDARD OPENING DIMENSIONS	Width - in. (mm)	24 (610)
	Depth - in. (mm)	24 (610)
	Height - in. (mm)	32-1/8 (816)
INTERNAL VOLUME Net. Cu. Ft. (L)		4.8 (136)
SHIPPING WEIGHT Lbs. (kg.)		195 (88)
ELECTRICAL SPECIFICATIONS	Electrical Supply	115 VAC/60 Hz/1 Ph
	Running Load Amps	1.9
	Electrical Connection	Cord connected
	Cord Plug Type	NEMA 5-15P
	Cord Length	6'
	Defrost Initiation	Automatic
	Defrost Type	Off cycle
	Thermostat	Digital
	Lighting Type	LED
REFRIGERATION SPECIFICATIONS	Refrigerant	R600a (62g)
	Expansion Device	Capillary Tube
	Temperature Settings F°(C°)	34° (1.1°) - 42° (5.6°) Factory Set Point 36° (2.2°)
	Heat Rejection (at 75°F)	450 BTU/hr
	Pull Down Capacity	525 BTU/hr
	Front Vented	Yes
PLUMBING		None Required

CABINET CONSTRUCTION	HB24RS-BS-STK
Cabinet Construction - Exterior	Top & sides are Stainless Steel. Back is Galvanized.
Cabinet Construction - Interior	Stainless Steel
Cabinet Insulation	Polyurethane-Ecomate. Wall Thickness 2" (foamed-in-place)

SHELVING	HB24RS-BS-STK
Black Vinyl-Coated Full Extension Shelves	2
Black Vinyl-Coated Full Extension Wine Shelves f/(8) 750ml Bottles	-

NOTE: This equipment is intended for the storage and display of non-potentially hazardous bottled or canned products only!

! WARNING: California Prop 65 Notice

These products may expose you to chemicals including Chromium, which are known to the state of California to cause cancer and birth defects or other reproductive harm. For more information on whether a product in this list contains these chemicals, please refer to the specific product page at perlick.com. Or to find out more about Prop 65, go to P65Warnings.ca.gov.

