
| - | | ☐ 2990 \ |
|-------------------|---------------------|----------|
| | | OPTIONS |
| | A | □ SNAP |
| | 1 | FEATURE |
| | | * FITS A |
| 3/4-14 UNS | | * SPRAY |
| | | * BLACK |
| | 7-1/2" | * BUILT- |
| | 7-1/2" [191.8mm] | * SHOW |
| | | SYSTEM |
| | HANDLE CLIP | 0.312 |
| 4-1/8" | J | * TEMP: |
| [103.8mm] \\\ ((© | | * PRESS |

ITEM NO.

APPLICATION:

JOB NAME:

QUANTITY:



| PRC | DUC | ΤΝΔ | м⊨∙ |
|-----|-----|--------|-------|
| LVC | טטט | 1 17/7 | uvi⊏. |

PRO SPRAY VALVE

CHECK BASE MODEL AND OPTIONS

SPEC. 2990 REV.

SPECIAL CONFIGURATION

MODEL:

W/ 2.65 GPM NOZZLE

OR MODIFICATIONS:

-IN SCRUB BRUSH

ES

- LL BRANDS
- Y NOZZLE THREADED INTO BODY
- STRENGTH BRONZE ALLOW HANDLE
- CDISH GUARD BUMPER
- IN SPRAY HANDLE CLIP
- ER SPRAY PATTERN

LIMITS

- 40°F MIN. TO 140°F MAX.
- PRESSURE 200 PSI MAX. STATIC
- * 2.65 GPM AT 80 PSI

SHIPPING WEIGHT

* 1.5 LBS



TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com