

Prodigy



Prodigy Plus® Modular Cube Ice Machine

The world's smartest cuber.

As the world's only self-monitoring cuber, the new Scotsman Prodigy Plus® cube ice machines make it easier than ever to maintain your equipment and save money. Whether it's the advanced ice level control or an optional feature board for guick diagnostics, this is ice-making re-imagined. And with intuitive technology like AutoAlert™ indicator lights, a reduced operational footprint and easy-access service from the front panel, Prodigy Plus® cubers are simply the smartest, most reliable way to create fresh-tasting ice — every time.

The Prodigy Plus® difference. • AutoAlert™ indicator lights for better visibility

- Operational footprint among the industry's smallest
- Industry-exclusive QR code instantly connects users to service information and warranty history
- One-touch cleaning reduces labor costs and saves time
- Front-located air filter for more efficient operation
- Self-aligning front panel for easy access to key components
- Patented WaterSense purge control automatically reduces scale buildup
- Patented Harvest Assist efficiently moves cube ice to the bin
- Smart-Board™ advanced feature module available for additional diagnostic capabilities
- Optional Vari-Smart™ ice level control allows operators to customize ice levels
- · Antimicrobial protection guards internal surfaces between cleanings
- A full range of water- and energy-saving features



24 Hour Volume Production

Air Cooled			Water Cooled			
70°F/21°C 50°F/10°C	Air Water	90°F/32°C 70°F/21°C	70°F/21°C 50°F/10°C	Air Water	90°F/32°C 70°F/21°C	
356/162 lb/kg		232/105 lb/kg	366/166 lb/kg		292/133 lb/kg	



B322S

Modular Bin Options

M 11	D' '	Bin Application		cl: warile
Model Number*	Dimensions W" x D" x H"	Capacity lb/kg	Finish	Ship Weight lb/kg
B322S	22 x 34 x 44**	370/168	Metallic	140/64

^{*} Contact Scotsman for bin top requirements. ** Add 6" Height for bin legs.













- 5 years parts and labor on the evaporator.
- 5 years parts on the compressor and condenser.

Warranty


- Warranty valid in North, South & Central America for commercial installations.
- Contact factory for warranty in other regions.
- · Residential Applications: 1 year parts and labor




- 101 Corporate Woods Parkway, Vernon Hills, IL 60061 •
- 1-800-SCOTSMAN Fax: 847-913-9844 www.scotsman-ice.com customer.relations@scotsman-ice.com •

C0322 - 300lb Cube Ice Machine


Prodigy Plus® Modular Cube Ice Machine




WATER COOLED BACK VIEW









Water Usage



Specifications

	Model Number ube Size: medium or small	Condenser Unit	Basic Electrical Volts/Hz/Phase	Max. Fuse Size or HACR Circuit Breaker (amps)	Circuit Wires	Min. Circuit Ampacity	Energy Consumption kWh/100 lb (45.4 kg) 90°F(32°C)/70°F(21°C)	Potable	b (liters/45.4 kg) Condenser)/70°F(21°C)
med.	C0322MA-1	Air	115/60/1	15	2	12.7	6.95	18.0/68.2	-
	C0322MW-1	Water	115/60/1	15	2	11.9	5.23	18.3/69.4	144.0/545.6
	LC0322MA-32	Air	208-230/60/1	15	2	6.1	6.95	18.0/68.2	-
	C0322SA-1	Air	115/60/1	15	2	12.7	6.95	18.0/68.2	-
Sm	C0322SW-1	Water	115/60/1	15	2	11.9	5.23	18.3/69.4	144.0/545.6
	C0322SW-32	Water	208-230/60/1	15	2	6.1	5.23	18.3/69.4	144.0/545.6



All Models

Dimensions (W x D x H):

Jnit: 22" x 24" x 23"

(55.9 x 61.0 x 58.4 cm)

Shipping Carton: 25.5" x 27.5" x 28"

(64.8 x 69.9 x 71.1 cm)

Shipping Weight: BTUs per hour: 155 lb / 70 kg 5,200

Refrigerant: R-404A



Accessories

Model Number	Description
KVS	Vari-Smart™ Ice Level Control - Program ice bin levels to match ice needs.
KSBU	Smart-Board™ Advanced Control - Use additional operational data for fast diagnosis.
KSBU-N	Smart-Board™ Advanced Control with Network - Network capable.
KPAS	Prodigy Advanced Sustainability Kit - Includes KVS and KSBU - N
KPPSA223	Prodigy Plus® Side Air Flow Kit for C0322 and C0522

Scotsman recommends all ice machines have water filtration. See Scotsman water filter specification sheet for details.



Operating Requirements

Minimum	Maximum	
50°F (10°C)	100°F (38°C)	
40°F (4.4°C)	100°F (38°C)	
-20°F (-29°C)	120°F (49°C)	
20 PSIG (1.4 bar)	80 PSIG (5.5 bar)	
-5%	+10%	
	50°F (10°C) 40°F (4.4°C) -20°F (-29°C) 20 PSIG (1.4 bar)	50°F (10°C) 100°F (38°C) 40°F (4.4°C) 100°F (38°C) -20°F (-29°C) 120°F (49°C) 20 PSIG (1.4 bar) 80 PSIG (5.5 bar)

Specifications and design are subject to change without notice.



