

UltraGold™ 18 Series

P20-18 with UltraClear™ Filtration

The UltraGold™ 18 gas fryer occupies the middle ground: not too big or too small.

This model has three 18 in. vats, each with a 70-110 lb. oil capacity. You also have the option to connect up to six vats.

Our UltraClear™ filtration system cleans shortening to increase food quality and extend oil life.

Our patented PAR-2 phased-array heat exchanger is perfect for menu items that require consistent, low temperatures over long periods of time, such as bone-in chicken. It's designed to direct heat through baffles and turns, resulting in efficient transfer of energy to the oil and even heat distribution, virtually eliminating recovery times.



Optional equipment shown

STANDARD FEATURES

- Energy Star® rated
- PAR-2 phased-array heat exchanger
- Thermostatic controls
- UltraClear™ filtration system
- Six fast-flow filter envelopes
- Three vats
- Stainless steel construction
- Pilotless electronic ignition
- Heavy-duty casters
- Drain cleaning rod and vat cleaning brush
- Two baskets per vat (each 16.37"L x 8"W x 6.75"D)

OPTIONS

- UltraStat® 23 computer controls
- UltraGuard™ automatic melt cycle with vat protection
- Add up to six vats

ACCESSORIES

- Vat covers
- Splash guards
- Basket lifts
- Triple baskets
- Fast-flow filtration pads
- Triple filtration
- Stainless steel filter screen
- Drain valve for filter tub
- Boil-out hose
- Shortening disposal line

Project _____

Item _____

Quality _____

Approval _____


Date _____



Ultrafryer®

UltraGold™ 18 Series

P20-18 with UltraClear™ Filtration



Sales ID#	Oil Capacity	Overall Size (H x D x W)	Nominal Vat Size	Total BTUH	Net Weight	Shipping Info
B-P20-18-3-UC	70-110 lb per vat (36 L)	40.82" x 41.47" x 58.5" (1037 x 1053 x 1486 mm)	18" x 18" (457 x 457 mm)	195,000	780 lb (353.8 kg)	F.O.B. Factory San Antonio, Texas
B-P20-18-4-UC	70-110 lb per vat (36 L)	40.82" x 41.47" x 77.87" (1037 x 1053 x 1981 mm)	18" x 18" (457 x 457 mm)	260,000	975 lb (442.3 kg)	F.O.B. Factory San Antonio, Texas
B-P20-18-5-UC	70-110 lb per vat (36 L)	40.82" x 41.47" x 97.25" (1037 x 1053 x 2470 mm)	18" x 18" (457 x 457 mm)	325,000	1,035 lb (469.5 kg)	F.O.B. Factory San Antonio, Texas
B-P20-18-6-UC	70-110 lb per vat (36 L)	40.82" x 41.47" x 116.62" (1037 x 1053 x 2962 mm)	18" x 18" (457 x 457 mm)	390,000	1,229 lb (557.5 kg)	F.O.B. Factory San Antonio, Texas

Determined in accordance with ASTM F2144 Standard Test Method for the performance of open vat fryers. Energy input rating 65,000 BTU's/hr

ASTM PERFORMANCE RESULTS


	Heavy Load
Idle Energy Rate (BTU/hr)	6,281
Cooking Energy Efficiency (%)	60.1

Based on a minimum of three test replicates.

HEATING ELEMENT & VAT CONFIGURATION



PAR-2 Heat Exchanger



3 to 6 vats

CONTROLLER ELECTRICAL REQUIREMENTS

120 V, 60 Hz 1 phase, 8.5 A

Electrical cord is 6' long and located on rear right-hand side (control circuit).

GAS SPECIFICATIONS

Gas	Gas Line For 3 Vats	Gas Line For 4 Vats	Gas Line For 5 Vats
7" water column NG	3/4"	1"	1-1/4"
14" water column LP			

FILTER SYSTEM

UltraClear filtration



© 2017 Ultrafryer Systems, Inc. Due to continuing engineering development and improvements, specifications are subject to change without notice.

Revision date: 1.30.2019

Ultrafryer®