



Model: _____ Item #: _____ Date: _____
 Project: _____ Qty: _____ Approved By: _____

Royal Series Gas Connector Kit #2

Gas Connector with Quick Disconnect & Restraining Kit



Product Description

The Krowne Metal Gas Connector is a stainless steel hose designed to be used with stationary and caster-mounted commercial kitchen equipment. Its design is convenient for equipment that is routinely moved for cleaning as features such as the rotational end pieces and the included restraining cable provide both ease and durability when moving large gas-supplied equipment.

The green antimicrobial PVC-coated protective layer allows for easy cleaning while the stainless steel corrugated tubing provides both flexibility and a strong internal structure that will last with enduring strength.

Standard Features

- Ends rotate for simple installation and durability
- Heavy duty stainless steel corrugated tubing flexibility for easy installation
- Heavy duty stainless steel radial wrap prevents hose from stretching
- PVC Protective coating with anti-microbial agent for easy cleaning
- Welded construction for added durability

Included Contents

① Gas Connector	Designed for moveable, caster mounted kitchen equipment
② Quick Disconnect	Easily disconnects gas hose to move equipment for maintenance and cleaning
③ Restraining Kit	Prevents hose from being pulled too far

Size Chart

Interior Size	Length	Model	BTU/hr*
1/2"	24"	P5024K2	87K
1/2"	36"	P5036K2	77K
1/2"	48"	P5048K2	68K
1/2"	60"	P5060K2	60K
1/2"	72"	P5072K2	55K
3/4"	24"	P7524K2	232K
3/4"	36"	P7536K2	218K
3/4"	48"	P7548K2	180K
3/4"	60"	P7560K2	158K
3/4"	72"	P7572K2	139K
1"	24"	P10024K2	414K
1"	36"	P10036K2	379K
1"	48"	P10048K2	334K
1"	60"	P10060K2	294K
1"	72"	P10072K2	279K
1-1/4"	24"	P12524K2	699K
1-1/4"	36"	P12536K2	615K
1-1/4"	48"	P12548K2	541K
1-1/4"	60"	P12560K2	476K
1-1/4"	72"	P12572K2	419K

Certifications



ANSI Z21.69 • CSA 6.16
Connectors For Movable Gas Appliances
 ANSI Z21.41 • CSA 6.9
Quick Disconnect Devices For Use With Gas Fuel Appliances
 UL567 Pipe Connectors For Flammable and Combustible Liquids and LP Gas

Restraining Kits are required by law for all movable gas equipment

Replacement Parts

Quick Disconnect



Interior Size	Model
1/2"	QD50
3/4"	QD75
1"	QD100
1-1/4"	QD125

Restraining Kit



Length	Model #
24"	R24
36"	R36
48"	R48
60"	R60
72"	R72