

QTI1+CR SYSTEM

FOODSFRVICE WATER TREATMENT SYSTEM

QTI1+CR: 170-52081 Replacement Cartridges: CTO-Q10 300-05828 CTOS-OCR 300-05832



APPLICATIONS

Steam & combi ovens

FEATURES • BENEFITS

- IsoNet® OptiPure's patented scaleinhibiting technology, helps protect equipment against scale and corrosion for the rated capacity of the system.
- Reduces maintenance frequency and cost, and extends equipment life.
- Gradient-density sediment filtration protects against dirt, rust and other debris.
- CTO-Q10 cartridge Activated carbon filtration protects equipment against corrosive chlorine.
- CTOS-QCR cartridge Catalytic carbon provides added protection against chloramines when present in water supplies and IsoNet provides scale inhibition.

- New manifold design provides fewer possible leak points.
- Sturdy, powder-coated mounting bracket and multi-function valve simplify installation.
- Multi-function valve provides:
 - Shutoff valve for quick and simple filter replacements
 - System bypass valve for easy system maintenance
 - Flush port to flush cartridges after installation
- Built-in pressure gauge allows visual monitoring of when filters need to be changed.
- Utilizes Qwik-Twist cartridges that make changing filters quick, easy and sanitary.

INSTALLATION TIPS

- Feed-water connection to system should be COLD only.
- Do not exceed system specifications for temperature and pressure.
- Allow 3" clearance below system for filter cartridge removal and cartridge replacement.
- To be used for treated water connection only.
- Detailed installation, operation and maintenance manual included with each system.

OPERATION TIPS

- Change cartridges on a regular six (6) month preventative maintenance program.
- Change cartridges when capacity is reached or when flow becomes too slow.
- Always flush the filter cartridge at time of installation and cartridge change.

SIZING

- Service Flow Rate: 2.5 gpm (9.5 lpm)
- Rated Capacity: 20,000 gals. (75,708 L)


QTI1+CR SYSTEM

170-52081

OTI1+CR: 170-52081

Replacement Cartridges: CTO-Q10 300-05828

CTOS-QCR 300-05832



SPECIFICATIONS

- Service Flow Rate
 Maximum 2.5 gpm (9.5 Lpm)
- Rated Capacity 20,000 gallons (75,708 L)
- Pressure Requirements
 10 125 psi (0.7 8.6 bar), non-shock
- Temperature 35 - 100°F (2 - 38°C)
- Overall Dimensions
 23.3" L x 14.3" W x 4.8" D
 59.2 cm x 36.3 cm x 12.2 cm

Inlet Connection

Inlet Connection: 1/2" MNPT

Outlet Connection

Outlet Connection: 1/2" MNPT

- Shipping Weight 9 lbs (4.1 kgs)
- Electrical Connection
 None required



System Tested and certified by IAPMO R&T to NSF/ANSI Standard 42:

AESTHETIC EFFECTS

Chemical Reduction Chlorine, Chloramine, Taste & Odor

Mechanical Filtration Nominal Particulate Class III

WARRANTY

Everpure water treatment systems by Pentair (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Pentair will provide a copy of the warranty upon request.

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Since the conditions under which our products may be used are beyond our control, we cannot accept any liability with respect to the improper installation, application and/or use of our products.



United States | 1040 Muirfield Drive | Hanover Park, IL 60133 | 800.942.1153 (US Only) 630.307.3000 Main | cseverpure@pentair.com | foodservice.pentair.com | Australia | 1-21 Monash Drive | Dandenong South, Vic 3175 | Australia | 011.1300 576 190 Tel | au.everpure@pentair.com

China | 21F Cloud 9 Plaza, NO 1118 | Shanghai, 200052 | China | 86.21.3211.4588 Tel | china.water@pentair.com

India | Boulevard, B-9/A, 7th Floor - Tower B Sector 62 | Noida - 201301 | 91.120.419.9444 Tel | indiacustomer@pentair.com

Europe | Pentair Water Belgium BVBA | Industriepark Wolfstee, Toekomstlaan 30, B-2200 Herentals | Belgium | +32.(0).14.283.504 Tel | sales@everpure-europe.com Japan | Japan Inc. | Hashimoto MN Bldg. 7F, | 3-25-1 Hashimoto, Midori-ku, Sagamihara-shi | Kanagawa 252-0143 | Japan | 81.(0)42.775.3011 Tel | info@everpure.co.jp Southeast Asia | 390 Havelock Road, | #04-01 King's Centre | Singapore 169662 | 65.6768.5800 Tel | cseverpure@pentair.com

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.