



Glass Door Counter Tops



VR-7-HC
(FORMALLY JUNIOR-1-HC)
Height..... 52.8125"
Length 21.0625"
Depth..... 23.50"
Cubic Ft..... 7
Liters..... 198
Bottles (20oz)..... 90
Cans (12oz)..... 216



VR-8-HC
(FORMALLY V-252-HC)
Height. 59.0625"
Length. 21.0625"
Depth 23.50"
Cubic Ft..... 8
Liters 227
Bottles (20oz)..... 120
Cans (12oz) 252



VR-10-HC
Height. 53.4375"
Length. 25.00"
Depth 22.50"
Cubic Ft..... 9.6
Liters 283
Bottles (20oz)..... 168
Cans (12oz) 336



Features

- Interior and exterior constructed of heavy duty white coated steel
- Polyurethane insulation with cyclopentane as blowing agent
- Double pane glass door with Low-E protection
- Illuminated top header sign (VR-8-HC)
- Externally mounted hinged glass doors
- Recessed door handle
- Heavy duty shelves with clips
- Heavy duty hinges with self closing mechanism
- Forced air evaporator for rapid temperature "Pull Down"
- Self contained heavy duty 134a condensing unit
- Energy efficient LED lighting
- UL Classified to ANSI/NSF 7



VR-12-HC
Height. 62.5625"
Length. 25.00"
Depth 22.50"
Cubic Ft..... 12
Liters 340
Bottles (20oz)..... 210
Cans (12oz) r432



VR-15-HC
Height..... 65.625"
Length..... 29.875"
Depth 26.00"
Cubic Ft..... 15
Liters 425
Bottles (20oz)..... 192
Cans (12oz) 504

| Model No. | Description | Voltage | Amps | Temp | HP | Est. Ship Weight |
|-----------|------------------|---------|------|-------------|-----|------------------|
| VR-7-HC | 1 Door/2 Shelves | 115 | 2.0 | 32°F - 39°F | 1/5 | 187# |
| VR-8-HC | 1 Door/3 Shelves | 115 | 2.2 | 32°F - 39°F | 1/5 | 205# |
| VR-10-HC | 1 Door/3 Shelves | 115 | 2.8 | 32°F - 39°F | 1/5 | 230# |
| VR-12-HC | 1 Door/3 Shelves | 115 | 2.0 | 32°F - 39°F | 1/5 | 235# |
| VR-15-HC | 1 Door/3 Shelves | 115 | 2.6 | 32°F - 39°F | 1/4 | 310# |



Technical Data / Glass Door

| Model # | VR-7-HC | VR-8-HC | VR-10-HC | VR-12-HC | V-15-HC |
|----------------------------|-----------------|-----------------|-----------------|-------------------|-----------------|
| Outside Dimensions | | | | | |
| Depth | 23.50" | 23.50" | 22.50" | 22.50" | 26.00" |
| Length | 21.0625" | 21.0625" | 25.00" | 25.00" | 29.875" |
| Height | 52.8125" | 59.0625" | 53.4375" | 62.5625" | 65.625" |
| Door Size | 21.75" x 42.25" | 20.63" x 38.50" | 26.25" x 43.00" | 25.00" x 52.6875" | 30.00" x 47.75" |
| Door Type | 1 swing | 1 swing | 1 swing | 1 swing | 1 swing |
| Inside Dimensions | | | | | |
| Depth | 18" | 18" | 18.50" | 18.50" | 21.6875" |
| Length | 17.5625" | 17.5625" | 21.50" | 21.50" | 25.25" |
| Height | 38.6875" | 45.3125" | 41.4375" | 51.00" | 45.88" |
| Shelf Size | 16.75"x16.75" | 16.75"x16.75" | 21.25"x17.50" | 21.25"x17.50" | 24.50"x19.50" |
| # of Shelves | 2 | 3 | 3 | 3 | 3 |
| Capacity: Cubic Foot | 7 | 8 | 10 | 12 | 15 |
| Specifications | | | | | |
| Operating Temperature | 32°F-39°F | 32°F-39°F | 32°F-39°F | 32°F-39°F | 32°F-39°F |
| Refrigerant | R290 | R290 | R290 | R290 | R290 |
| Compressor Size HP | 1/5 | 1/5 | 1/5 | 1/5 | 1/4 |
| Voltage | 115 | 115 | 115 | 115 | 115 |
| Amperage | 2.0 | 2.2 | 2.8 | 2.0 | 2.8 |
| Cord and Plug | yes | yes | yes | yes | yes |
| Shipping Dimensions | | | | | |
| Depth | 28.00" | 28.00" | 28.00" | 28.00" | 30.00" |
| Length | 25.00" | 25.00" | 30.00" | 30.00" | 33" |
| Height | 60.00" | 66.00" | 60.00" | 66.00" | 68.00" |
| Gross Weight lbs. | 187 | 205 | 230 | 235 | 310 |
| Cubic feet | 24 | 26 | 29 | 32 | 35 |

- Cases are designed to operate at 75°F and 55% relative humidity.
- Specification subject to change without notice.

