




BLS-4FTD-2



TOUCH digital programmable controls:



- 9
BAKING
STEPS
- 0 - inf
TIMER
- 120° - 500° F
TEMPERATURE
- 0-20-40-60-80-100%
HUMIDITY
- 2
FAN
SPEEDS
- PROOFER
CONTROL
- 99 PROGRAMS
- WI-FI
- DATA DRIVEN
COOKING -
CHAIN BASED
APPLICATION



OST-195-CS
Short Heavy-Duty Stand with Wheels
for Full Size Ovens

- Handles 5 full size sheet pans (not included)
- Can hold 2 full size Cadco ovens with Stacking Kit
- Aluminum

Full 18x26 Pans

Made to Cadco Ltd. specifications by UNOX S.p.A., Italy • NSF, MET to UL & CSA Standards
We recommend that the end user have a standard ice-machine filter when using a humidity hookup.

Bakerlux Station Includes:

Model	Color	Volts	Watts	Amps	Unit Dimensions
XAFT-04FS-TD	Stainless	208-240	7600	32	w:31 1/2", h:19 ^{5/8} ", d:35 ^{1/2} "
OST-195-CS	Stainless		N/A		w:31.71" h:21.5 x d:27

Shipping Unit Dimensions

- 2 SKIDS CLASS 200
- 1 SKID 44X38X56 260 POUNDS -1 OVEN ,HOOD AND STAND
- 1 SKID 44X38X29 200 POUNDS – 1 OVEN AND STACKING KIT

