

TRANSPORT and DELIVERY CABINETS | STAINLESS STEEL

Efficient delivery is easily achieved with time-saving transport cabinets.

- Unibody construction keeps the cabinet balanced and stable during transport
- Tubular Stainless steel welded base frame provides extra strength and support
- Rack assembly for 18" x 26" (457 x 660) sheet pans removes easily for cleaning.
- Fixed ledges allow 3" spacing for a variety of food
- Universal ledges are removable and height-adjustable to accommodate a variety of pans and trays.

FACTORY INSTALLED OPTIONS:

- Full perimeter bumper
- Vented door
- Left hand door hinging
- Magnetic Latch
- Transport door latch
- Transport package. Includes: 2 fixed, 2 swivel 5" (127), 2" (51) wide extra-load casters, full perimeter bumper, transport latch
- All-swivel Lake-Glide® casters. Floor lock, includes 6" (152) Lake-Glide casters
- Additional universal ledges
- Door with clear polycarbonate panel



Model #6536



Freight Class: **100**

Model	Ledges Provided	Overall Size			Case Weight Lbs. (Kg)	Case Cube Cu. ft. (m³)
		W	D	H		
Ledge Assembly for 18" x 26" Sheet Pans						
6532*	7 ea.	25-1/2" (648)	34" 864	32" 813	125 (57)	24.4 (.64)
6533	11 ea.	25-1/2" (648)	34" 864	45" 1143	165 (75)	33.7 (.93)
6534	16 ea.	25-1/2" (648)	34" 864	60" 1524	205 (93)	43.9 (1.21)
6536	19 ea.	25-1/2" (648)	34" 864	69" 1753	230 (104)	50.1 (1.38)
Universal Ledges						
6537*	5 ea.	28" (711)	34" 864	33" 838	140 (59)	28.5 (.79)
6538	7 ea.	24-1/4" (616)	29-3/4" 755	42" 1067	150 (77)	35.2 (.97)
6539	11 ea.	24-1/4" (616)	29-3/4" 755	60" 1524	215 (104)	48.3 (1.33)
6540	13 ea.	24-1/4" (616)	29-3/4" 755	69" 1753	255 (114)	55.0 (1.52)

TRANSPORT and DELIVERY CABINETS | ALUMINUM

Efficient delivery is easily achieved with economical aluminum transport cabinets.

- Rugged, reinforced door safeguards contents
- All-welded construction with extra gussets welded in all corners to prevent alignment "racking"
- Aluminum alloy construction adds strength without the weight, so transport is safe and easy
- Durable 1/2" (13) wide extruded aluminum ledges
- Rust proof and corrosion resistant

FACTORY INSTALLED OPTIONS:

- Clear polycarbonate door
- Corner Bumpers, non-marking gray rubber strip mounted to the corners of base. Adds 2" (51) to the width and depth of the unit.
- Perimeter Bumpers, non-marking gray rubber strip affixes around the unit's base. *Note: This option adds 2" (51) to the width and depth of the unit.*
- Push Handle
- Lake-Glide 5" (127) casters with brakes (set of 2)



Model #5529



Freight Class: **150**

Model	Sheet Pan Capacity		Ledge Spacing	Overall Size			Case Weight Lbs. (Kg)	Case Cube Cu. ft. (m³)
	Full	Half		W	L	H		
5527	20 ea.	40 ea.	1-1/2" (38)	20-7/8" (530)	27-5/8" 702	38" 965	72 (32.4)	14.4 (.4)
5529	32 ea.	64 ea.	1-1/2" (38)	20-7/8" (530)	27-5/8" 702	56" 1422	106 (47.7)	21.6 (.6)
5531	40 ea.	80 ea.	1-1/2" (38)	20-7/8" (530)	27-5/8" 702	68" 1727	113 (50.9)	26.4 (.73)

Lake-Glide Casters: 5" (127) - All swivel; No-Mark, polyurethane are standard.