

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

Chef Base Refrigerator - Flat Top

Patented Self-Cleaning Condenser



Model : PRCBE-72R-N-FT

Chef Bases PRO Series



\equiv FEATURES & BENEFITS =

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Digital temperature display on front panel

Strong body and durable construction Built with heavy duty 16 ga. stainless steel, Chef Base top is

manufactured of one-piece reinforced stainless steel to ensure durability.

Countertops

PRCBE-36/48/60R-N-FT supports up to 788 pounds of equipment. PRCBE-72/84/96R-N-FT supports up to 1,192 pounds of equipment.

Each left side drawer accommodates up to 6" deep two (2) full size pans and each right side drawer accommodates up to 6" deep one (1) full size pan with three (3) 1/6 size pans

- Top is insulated to eliminate heat transfer to the interior of cabinet
- Side mount compressor unit Compressors positioned on the side of the units makes servicing our units easy. Our front air intake feature also allows this model to be highly efficient in narrow spaces.
- Durable stainless steel drawers
- High-density polyurethane insulation The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.
- Stainless steel flat top
- Hot gas condensate system
- Full length drawer with gasket guard
- Drawer slider load capacity up to 180 lbs
- Magnetic snap-in gasket
- Refrigerator holds 33°F ~ 38°F for the best in food preservation

size pan with three (3) 1/6 size pans					NATURAL(Refrigeran	
Model	Drawers	CU./FT.	HP	AMPS	Crated Weight (lbs.)	$L \ge D^* \ge H^{\dagger}$
PRCBE-72R-N-FT	4	12.14	1/4	3.3	473	721/8 x 331/2 x 213/8

Ver.20240501 Printed in U.S.A.

* Depth does not include 1/2" for drawer handles. † Height does not include 4-1/2" for caster height.

Chef Base Refrigerator - Flat Top

Model : PRCBE-72R-N-FT

ELECTRICAL DATA					
Voltage		115/60/1			
Plug Type		NEMA 5-15P			
Full Load Amperes		3.3			
Compressor HP		1/4			
Cord Length (ft.)		9			
Refrigerant		R-290			
DIMENSIONAL DATA					
Ext. Length Overall (in.)		721/8 (1832mm)			
Ext. Depth Overall (in.)*		331/2 (852mm)			
Ext. Height Overall (in.) [†]		213/8 (544mm)			
# of Drawers		4			
# of Pans	Тор	(Left) (1) 1/3 size, (10) 1/6 size (Right) (9) 1/6 size			
	Bottom	(Left) (12) 1/6 size (Right) (9) 1/6 size			
Net Capacity (cu. ft.)		12.14			
Net Weight (lbs.)		407			
Gross Weight (lbs.)		473			

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection. * Depth does not include 1/2" for drawer handles. † Height does not include 4-1/2" for caster height.

• WARRANTY : ⁵ Year Parts and Labor Warranty 7 Year Compressor Warranty

STANDARD FEATURES


- Anti-corrosion coated evaporator
- Self-contained system
- 4" dia. swivel casters

OPTIONAL ACCESSORIES


- 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600

PLAN VIEW


(unit : inch)



TOP VIEW



FRONT VIEW



Ver.20240501

■ Turbo Air: 800-627-0032 ■ Radiance: 800-500-3519

Warranty: 800-381-7770 **AC**: 888-900-1002



