

AFZ2PVBIADADL2B



32" x 19.75" x 22.63" (H x W x D)

Performance series Pharma-Vac 2.47 cu.ft. ADA height purpose-built vaccine storage freezer designed for recessed or freestanding installation, with a NIST calibrated temperature logger (DDL)

Highlights:

NIST calibrated DDL included for accurate temperature logging

Sized just under 32" high to fit under lower ADA compliant counters

Intelligent microprocessor digital temperature controller

Product Features:

| | |
|------------------------------------|--|
| Performance Series freezer | Purpose-built all-freezer for vaccine storage in medical, pharmaceutical, and life science applications |
| Purpose-built design | Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines |
| ADA Compliant | Just under 32" tall designed to fit under ADA compliant counters |
| Digital data logger (DDL) included | Accucold DL2B data logger is NIST calibrated in our ISO/IEC 17025:2017 laboratory, with user-set logging intervals, a large LCD readout of the current and high/low temperature, and virtually unlimited storage through internal memory and a convenient USB drive; for additional information on this logger's features, view the DL2BKit on our website |
| Recessed or freestanding use | Versatile design allows recessed installation under counters or freestanding use |
| +/-1°C Variation | The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period |
| Commercial design | Meets UL-471 commercial standards |
| Adjustable temperature | Intuitive controls let you adjust the interior temperature between -30°C to -10°C |
| Temperature alarm | Visual and audible alarms alert if the interior temperature rises or falls out of set range |

AFZ2PVBIADADL2B Specifications:

| Overview | |
|----------------------------|--------------------|
| Height of Cabinet | 32.0" (81 cm) |
| Width | 19.75" (50 cm) |
| Width with Door Open | 20.25" (51 cm) |
| Depth | 22.63" (57 cm) |
| Depth with Handle | 24.38" (62 cm) |
| Depth with door at 90° | 41.25" (105 cm) |
| Capacity | 2.47 cu.ft. (70 L) |
| Defrost Type | Manual |
| Door | White |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Amps | 1.3 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 99.0 lbs. (45 kg) |
| Shipping Weight | 110.0 lbs. (50 kg) |
| Parts & Labor Warranty | 2 Years |
| Compressor Warranty | 5 Years |
| UPC | 761101104034 |
| Freezer | |
| Door Swing | RHD |
| Reversible | Factory Reversible |
| Interior Height | 22.0" (56 cm) |
| Interior Width | 14.25" (36 cm) |
| Interior Depth | 15.5" (39 cm) |
| Shelf Type | Wire |
| Shelf Qty | 4 |
| Adjustable Shelves | Yes |
| Thermostat Type | Digital |
| Interior Light | Yes |
| Refrigerant Type | R290a |
| Refrigerant Amount | 1.31 oz. |
| High Side PSI | 280.0 |
| Low Side PSI | 130.0 |
| Compressor Step Height | 6.13" (16 cm) |
| Compressor Step Width | 14.25" (36 cm) |
| Compressor Step Depth | 7.5" (19 cm) |

Temperature Range

