



DXP612-U



DINEX SUPERIOR FOUNDATION

Featured on our toughest racks: Two 12 gauge aluminized steel reinforcing channels support our .090" thick aluminum bottom panel. The edges are formed and rolled to create a built-in bumper and plate casters make this the strongest foundation in the industry.

Dinex Universal Angle Racks are designed for in-house foodservice facilities, bakeries, restaurants and high-activity operations handling trayed product. Roll-in sizes are available for walk-in refrigerators or freezers. Our fully welded frame and 1/2" aluminum tie bar avoids distortion and gives greater side-to-side strength.

PAN GLIDES

- Universal ledge angles set at 3" or 5" spacing
- Holds sheet pans or steam table pans
- Weld along entire edge of glides

TIE BARS AND CONTINUOUS WELD

- 1/2" extruded aluminum tie bar keeps rack square
- Adds rigidity and stability to rack
- Two tie bars per unit
- No gaps to promote bacterial growth
- Solid Bottom

MODEL NUMBER

- DXP612U
- DXP620U
- DXPR618U (Roll-in)

DIMENSIONS

- DXP612-U - 27 1/2"L x 24"W x 69"H
- DXP620-U - 27 1/2"L x 24"W x 69"H
- DXPR618-U (Roll-in) - 27 1/2"L x 24"W x 64 3/4"H

SOLID BOTTOM

- Rolled edge acts as bumper
- 12 gauge reinforcing caster channel eliminates twisting
- Fully welded corners
- Greatly enhances rack strength
- .125" thick aluminum

SUPERIOR CORNER SUPPORTS

- .190" thick gussets provide superior strength
- Extruded 3-sided channel support
- All sides fully welded

HEAVY-DUTY CASTERS

- Plate casters for added rigidity and stability
- 5" x 1-1/4" sealed wheels
- Delrin bearing, each with 350 lbs. capacity
- Maximum resistance to chemicals, acids, bases, alcohol, water and steam
- Maximum low temperature flexibility for superior performance, even in freezing temperatures


WARRANTY

- One year parts and labor. Warranty is detailed on inside front cover of the price list.

We do not accept returns on any Dinex equipment or Dinex custom products. Please contact your local Dinex rep to ensure order accuracy prior to ordering.

Universal Angle Rack

Aluminum



Model#	Length	Width	(B) Height	(A) Channel Spacing (in.)	Shipping Wt. (lbs)	Tray Capacity		Pan Capacity 12 x 20		
						18x26	14x18	2.5	4	6
DXP612U	27-1/2"	24"	69"	5"	95	12	24	24	12	6
DXP620U	27-1/2"	24"	69"	3"	110	20	40	20	10	10
DXPR618U	27-1/2"	24"	64-3/4"	3"	67	18	36	17	9	9

R is roll-in height.

*Rack capacities are for 18" x 26" sheet pans

Height includes casters.

Custom height sizes and glide spacing available.

Typical freight class: 100

RACKS OPTIONS / ACCESSORIES PART NUMBER

Option	Description
<input type="checkbox"/> DXPPS	Pan Stop
<input type="checkbox"/> DXPEMB	Personalized Embossment (12 letters per line)
<input type="checkbox"/> DXPFLL	Floor Lock
<input type="checkbox"/> DXPPH	Push Handle
<input type="checkbox"/> DXPY5	5" Polyurethane Casters (set of 4)

Option	Description
<input type="checkbox"/> DXPPB	Non-Marking Rubber Bumpers - Corner (set of 4)
<input type="checkbox"/> DXPPB	Non-Marking Rubber Bumpers - Full Perimeter
<input type="checkbox"/> DXPPWB	Wheel Brakes (set of 2)
<input type="checkbox"/> DXPS2	Heavy-duty Casters (set of 4)
<input type="checkbox"/> DXPPV	Vertical Bumpers

I-8 SPEC

DINEX
www.dinex.com

4711 E. Hefner Road
Oklahoma City, OK 73131
800.654.8210
405.475.5600

LIMITED WARRANTY: DINEX warrants to the original purchaser parts and labor for a period of twelve (12) months from the date of purchase. See manufacturer's complete warranty for details.

It is our policy to build equipment which is design certified by companies that have been accredited at the Federal Level by the Occupational Safety and Health Agency (OSHA) and ANSI as a National Recognized Testing Laboratory. These companies include CSA International, Underwriters Laboratories, and the National Sanitation Foundation. However, a continuing program of product improvement makes it necessary to submit new models to the agencies as they are developed. Consequently, all models may not bear the appropriate labels at all times.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Information is not for design purposes.