







All around work horse! Rugged, welded construction. Shelf corners welded continuously at all points (over 41/2" welding at each corner). No crevices for dirt to collect.

SPECIFICATIONS

Utility Caddy to be Model	as manufactured	by Caddy Cor	poration of Ame	rica.
Frame of 1" O.D. 16 ga. stainless steel tub				
sides, flanged down to form a 134" wide of	channel. Shelf corne	ers to be noto	hed to fit conto	ur of
tubular frame, to eliminate unsanitary cre	vices and are to be	continuously	welded to legs a	at all
contact points. Casters 4" heavy duty, of	double ball bearing	swivel with	3/4" solid stems	and
polyurethane tires. All s.s. to be type 304.	No. 4 finish.			

The "A" series may be used for storage of menu holders or disposables. The larger cart ("B" series) is recommended for collecting reject trays at the end of the conveyor.


	"A" SERIES 34" long x 22" wide. Shelf size 32" x 20"	"B" SERIES 38" long x 26" wide. Shelf size 36" x 24" with s.s. crossbracing	SHELF CLEARANCE	O/A HEIGHT
2 shelves	☐ T-202-A	☐ T-202-B	181/4"	34¾"
3 shelves	☐ T-203-A	☐ T-203-B	81/4"	34¾"

ACCESSORIES (optional extra)

- □ 5" Polyurethane Tires, ACC-63, in lieu of 4" polyurethane.
- ☐ Circular Bumpers, ACC-38. add 4" to overall length and width
- ☐ Caster Brakes, ACC-41, on two diagonal casters.
- ☐ Plastic Tote Box, PL-1520, 15" x 20" x 5".

BEVERAGE CADDY

MODEL T-502



- Prepare hot or cold beverages in kitchen and wheel them to service areas
- · Perfect for conference rooms, office coffee service, schools and churches

SPECIFICATIONS

☐ Beverage Caddy to be **Model T-502**, as manufactued by Caddy Corporation of America. Frame of 1" O.D. 16 ga. seamless s.s. and shelf of 18 ga. s.s. with raised rounded edge on all sides, flanged down to form a 11/2" channel. Shelf corners die notched to fit contour of tubular frame, eliminating unsanitary crevices. Shelf continuously welded to legs at all contact points. Top, apron and drain trough 16 ga. s.s. Lower deck with inverted V curb on all four sides. Drainer section dropped 8" to give clearance for filling of pitchers. Perforated drainer to be 16 ga. s.s. and removable. Drain pan with drip faucet. Double ball bearing 4" casters, all swivel, two with foot brakes. Top size 34" long x 22" wide and 35" high overall.

ACCESSORIES (optional extra)

- Revolving Leg Bumpers ACC-38. Adds 4" to overall length and width.
- ☐ Plastic Tote Box PL-1520. 15" x 20" for napkin wrapped silverware.





