SINKS AVAILABLE

412, 414, and 314 Series

One- To Four-Compartment

Miscellaneous

314 Series Corner Convenience Store Lavatory Mop Sinks Mop Sink Storage Cabinet Stainless Steel Fabricated

Counter Drop-In

With Self Rim Design

Hand Sinks

Electronic - Battery Power
Electronic Eye Hand Sinks
- AC Power
Hand Wash Sinks
Physically Challenged
Space-Saver Series
Traditional
With Side Splashes
With Standard Towel Dispenser and/or
Soap Dispenser

OEM Sink Bowls

Drawn Bowl Fabricated Straight Wall

Special Purpose

Economical
With Deck Mount Faucet
With Waste Receptacle
With 8" Centerline
Faucet/Holes

SPEC-MASTER®

FFN Series Flush Front Supermarket Meat-Platter

SPEC-MASTER® FN Series Coved Corner

One- To Four-Compartment

Utility

Detachable Drainboards One- To Four-Compartment



Sink and Hand Sink Accessories



FAUCETS HAND SINKS



STANDARD - 4" Center (except #313075)

Description	Model #
splash mounted, gooseneck (A.)	303987
- wrist handles for #303987	307120
splash mounted with wrist handles, gooseneck	306495
deck mounted, gooseneck (B.)	302004
deck mounted, (C.) 8" spout	301248
drinking bubbler (D.)	318495
splash mounted, gooseneck. 8" center	313075

REPAIR KIT (E.) - for Faucets #303987, 302004, & 301248 only

DescriptionModel #consists of hot/cold stems,
handles, seats, bonnet nuts,
and 0-rings303975

T&S EXTRA HEAVY DUTY

Description	Model #
splash mounted, gooseneck (F.)	306134
splash mounted, wrist (G.) handles, gooseneck	313305

SPOUTS/SPOUT ASSEMBLIES (H.)

plash mounted replacement gooseneck for 120V AC electronic or pedal-operated model 312162

BATTERY-POWERED ELECTRIC-EYE

Describuon	Minne! #
splash mount, with 6-volt	326014
battery and built-in low battery ind	icator
Upgrade: T&S splash mount, (I.)	356128

with battery and AC adapter for dual operation

The industry's CLEAN LEADER.

Customer Service is available 8:00 am to 6:00 pm EST, Mon. - Fri.

Phone 1-800-441-8440

100 Industrial Boulevard • Clayton, Delaware 19938-8903 U.S.A.



STANDARD - 8" Center, Splash Mounted

Description	Model #
8" spout, standard	313918
12" spout, standard (A.)	300716
14" spout, standard	300804
16" spout, standard	313919
12" spout, heavy duty (B.)	301001
14" spout, heavy duty	301002
19" double-jointed spout (C.)	301003
gooseneck, 8" center (D.)	313075

- WITH WRIST HANDLES

Description	Model #
deck mounted, 4" center, (E.)	301005
standard	
deck mounted, 4" center, heavy duty	301004

REPAIR KITS

- FOR FAUCETS #313918 & 313919

Consists of	Model #
hot/cold stems, handles, seats,	304146
bonnet nuts, and O-rings	

- FOR FAUCETS #300716 & 300804

Consists of	Model #
hot/cold ceramic cartridge	368421

T&S EXTRA 8" Center, Splash Mounted HEAVY DUT

Description	Model #
8" spout	313920
10" spout (F.)	340380
12" spout (G.)	313293
14" spout	313294

- WITH WRIST HANDLES

Description	Model #
deck mounted, 4" center, (H.)	313304
gooseneck	

More accessories mean more design options for you...So you'll have more efficient work areas along with IMPROVED HYGIENE.



Visit Us @ http://www.eaglegrp.com



1-302-653-2065



PRERINSE UNITS AND COMPONENTS

STANDARD -

Description	Model #
splash mounted spray (A.)	300719
deck mounted spray (B.)	300718
faucet add-on with 12" spout (C.)	301189
wall bracket (D.)	301190
prerinse hose, 36" length (E.)	313116
prerinse spray valve (F.) assembly for spray units #300718 and 300719	313323
#3007 TO AIIU 3007 T9	

T&S EXTRA HEAVY DUTY -

Description	Model #
splash mount spray unit (G.) with wall bracket	313296
deck mounted spray (H.) with wall bracket	313295
faucet add-on with 12" spout (I.)	313297

SINK COVERS FN Series Sinks only

Description	Polyboard (J.)	S/S (K.)
14" x 10"	313207	321555
16" x 20"	351584	351585
20" x 18"	335377	346175
20" x 20"	326267	305428
22" x 22"	313204	321557
24" x 18"	326268	326270
24" x 24"	313205	321558
28" x 20"	326269	326271

LEG COMPONENTS

Description	Model #
19" s/s leg for utility sinks (L.)	300315
s/s flanged bullet feet (M.)	313835
s/s bullet feet (N.)	300692
plastic bullet feet	300293

The industry's CLEAN LEADER.

VALVES HAND SINKS

SHUT-OFF (A.)

Description	Model #
shut-off push bar	349921

TEMPERATURE ADJUSTMENT ("Mixing Valve") (B.)

Description	Model #
built-in check valves to prevent	326015
backflow and adjustment screw	
valves to mix hot and cold	

FAUCET-MOUNT EMERGENCY EYE WASH UNIT

Description		Model #
pull valve activates fountain	(C.)	326272
-anti-scald valve (D.)		373848

ANTI-SCALD VALVE (E.)

Description	Model #
1/2 " NPT, 100-145°F	326696
<u>IMPORTANT</u> : Not for use with emerge	ncy eye wash unit.

NON-ADJUSTABLE Y-INLET MIXING VALVE (F.)

Description	Model #
male connection;	342938
threads are 9/16-24 UNEF	

PEDAL VALVES

Description	Model #
KNEE PEDAL VALVE	
double (G.)	313481
single (H.)	351738
FOOT PEDAL VALVE, FLOOR MO	UNT
double (I.)	300604
single (J.)	355994

TEMPERING VALVE (K.)


Description	Model #
thermoplastic body, 3/8" male	375612
compression fittings, 80°F-120°F,	
0.5-2.5 gpm, built-in check valve	



Antibacterial surface. Screws onto faucet aerator. Polished chrome finish.



For hand sinks with AC-powered electric faucet or sinks with single pedal valves. Cast brass body. 3/8" all connections.



Fits in place of standard aerator on spout. Comes with two dust covers. Polished chrome finish.



This is the only anti-scald valve to be used with faucet-mount emergency eye wash unit. Meets ANSI Z358.1 standard.



Automatic shutdown with either hot or cold water failure.



Standard on electronic hand sinks and hand sinks with single pedal valves only. Chrome-plated brass body.









Maximum output of 120°F. Maximum pressure of 150 psi. ASSE 1016 and 1070 listed.

Visit Us @ http://www.eaglegrp.com



Fax 1-302-653-2065



TOWEL/SOAP DISPENSERS

Description	Model #
towel dispenser with - conventional soap dispenser (A.)	DP-10
- electric eye soap dispenser (B.)	DP-20
towel dispenser, wall mounted (C.)	318496
touchless towel dispenser (D.)	352854

SOAP DISPENSERS

Description	Model #
conventional (E.)	300602
wall mounted with electric eye (F.)	359752
deck-mount, 16-oz. (G.)	324074

HAND SANITIZING (H.) DISPENSER

Description	Model #
Purell/TFX, wall mounted	352852

NAIL BRUSH AND HOLDER (I.)

Description add suffix* #

infectious-control nail brush made of FDA-approved material, splashmount stainless steel nail brush holder *Example: HSA-10-F-NB

WASTE RECEPTACLE (J.)

for Models: add suffix* #

HSA-10: HSA-10-F: HSA-10-FA: HSA-10-FDP; HSA-10-FE; HSA-10-FDPE; HSA-10-FDPEE; and HSA-10-FW

*Example: HSA-10-F-T

HOT WATER HEATER (K.)

for Models: add suffix* #

HSA-10; HSA-10-F; HSA-10-FA; HSA-10-FDP; HSA-10-FE; HSA-10-FDPE: HSA-10-FDPEE: HSA-10-FA-P, and HSAD-10-F

*Example: HSA-10-F-WH

The industry's CLEAN LEADER.

Customer Service is available 8:00 am to 6:00 pm EST, Mon. - Fri.

> Phone 1-800-441-8440 100 Industrial Boulevard • Clayton, Delaware 19938-8903 U.S.A.



FACTORY-INSTALLED

Description	add suffix* #
left end splash only	-LS
right end splash only	-RS
left and right end splash (A.)	-LRS
*Example: HSA-10-F-RS	

FOR FIELD INSTALLATION (B.)

Description	Model #
self-adhesive side splash	HSA-SSK
can be used for right and	left application

WALL BRACKETS (c.)

Description	Model #
side mounting, one pair does not fit Space Saver models	606396

SKIRT ASSEMBLY (D.)

Description	Model #
HSA-10; HSA-10-F; HSA-10-FA;	606215
HSA-10-FDP; HSA-10-FE; HSA-10-FDPE;	
HSA-10-FDPEE; and HSA-10-FW	
HSAN-10-F and HSAND-10-F	607560

DRAINS	
Description	Model #
polymer lever drain fits (E.) 3-1/2" diameter holes Max. flow rate: 11 gallons per min.; 660 g	319931
overflow assembly for lever drain #319931	319932
1-1/2" drain assembly, (F.) fits 2" dia. hole	300886
Max. flow rate: 12 gallons per min.; 720 g	allons per hr.
mini crumb cup for 1-1/2" drain	300966
s/s basket drain assembly fits 3-1/2" dia. holes w/crumb cup Max. flow rate: 18 gallons per min.; 1080 g	300287 gallons per hr.
cast metal lever drain with overflow assembly, with 7-1/4" long lever, fits 3-1/2" dia. holes	347771



OPTIONAL MICROGARD® FOR HAND SINKS

Add suffix #: -MG

An antimicrobial agent which contains built-in protection to retard the growth of a broad range of bacteria, mold and mildew on the surface that cause stains, odors and degradation.

OPTIONAL ELECTROPOLISHING FOR HAND SINKS

Add suffix #: -EP

Attractive appearance. Improved surface finish is more corrosion-resistant. Reduced product adhesion. Easier to keep clean.

Visit Us @ http://www.eaglegrp.com





PLUMBING

- for Hand Sinks & Sinks

Description	Model #	
tail piece, nickel-plated (A.)	300791	
P-trap, nickel-plated (B.)	300789	

90° Short Elbows for Splash-Mt Faucets(C.) Ideal for all sinks with shallow backsplash!

Descripti	o n	Model #
set of two	1/2" NPT female x male	376740

- for Sinks ONLY

Description	Model #
anti-siphon vacuum breaker (D.)	313832
backflow preventer (E.)	313834

DRAINS	
Description	Model #
lever handle drain with (F.) 1-1/2" or 2" NPS connection	300720
Max. flow rate: 27 gallons per min.;	1620 gallons per hr.
lever handle drain with 2" NPS connection	300721

Max. flow rate: 32 gallons per min.; 1920 gallons per hr.

lever handle drain with 300722 2" NPS connection and overflow

Max. flow rate: 32 gallons per min.; 1920 gallons per hr. twist handle drain with (G.) 341189*

1-1/2" or 2" NPS connection Max. flow rate: 27 gallons per min.; 1620 gallons per hr.

336002* twist handle drain with 2" NPS connection

Max. flow rate: 32 gallons per min.; 1920 gallons per hr. twist handle drain with 341190*

2" NPS connection and overflow

Max. flow rate: 32 gallons per min.; 1920 gallons per hr. 369653

nickel-plated brass rotary drain with 1-1/2" or 2" NPS connection

Max. flow rate: 40 gallons per min.; 2400 gallons per hr.

crumb cup strainer with (H.) 300287 1-1/2" outlet

Max. flow rate: 18 gallons per min.; 1080 gallons per hr.

Twist handle bracket, for use with twist handle drain, should be ordered as sink option "-TB" at time of sink order.

©2012 EAGLE GROUP

EG7005 Rev. 01/12



