

## **SBC58BLBIADACMTWIN**



32.25" x 23.63" x 22.75" (H x W x D)

Built-in undercounter ADA height commercially listed dual tap combo nitro/cold brew coffee dispenser with stainless steel door and black cabinet

## **Highlights:**

32 inch height fits under lower ADA compliant counters

Commercial grade tap kit includes everything you need to serve both flat iced cold brew and creamy nitro-infused cold brew drafts

Commercially listed to NSF-7 standards

## **Product Features:**

Dispenses both flat and nitro-infused coffee	Unique combination stout and standard tap system allows you to serve both flat iced cold brew and nitro-infused drafts from two cornelius kegs	
ADA compliant height	Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters	
Built-in capable	Front-breathing design allows fully recessed installation under counters	
Commercially approved	Commercial grade tap kit includes a dual tap draft tower with a standard and stout tap, Nitrogen tank, dual gauge regulator, and connections for ball lock Cornelius kegs	
Complete tap kit	Commercial grade tap kit includes a stainless steel stout tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs	
Dual tap system	Twin style draft tower allows you to serve from two cornelius style kegs	
Stainless steel wrapped door	304 grade stainless steel for a professional look with lasting durability	
Professional handle	Thin handle with common 14mm diameter in brushed stainless steel mounted horizontally	
Adjustable thermostat	Interior dial thermostat ensures easy temperature management	







## **SBC58BLBIADACMTWIN Specifications:**

Overview			
Height of Cabinet	32.0" (81 cm)		
Height to Hinge Cap	32.25" (82 cm)		
Width	23.63" (60 cm)		
Depth	22.75" (58 cm)		
Depth with Handle	24.25" (62 cm)		
Depth with door at 90°	45.0" (114 cm)		
Capacity	5.5 cu.ft. (156 L)		
Defrost Type	Automatic		
Door	Stainless Steel		
Cabinet	Black		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Sanitation	ETL-S		
Amps	1.2		
Voltage/Frequency	115 V AC/60 Hz		
Weight	110.0 lbs. (50 kg)		
Shipping Weight	120.0 lbs. (54 kg)		
Estimated Time to Ship	3 to 5 days		
Parts & Labor Warranty	1 Year		
Compressor Warranty	5 Years		
Kegerator			
Door Swing	RHD		
Reversible	Yes		
Tap Kit	Yes		
Number of Taps	2		
Theorem and AT			
Thermostat Type	Dial		
Thermostat Type Interior Light	Dial Yes		
<del></del>			
Interior Light	Yes		
Interior Light Fan Type	Yes Exterior		
Interior Light Fan Type Refrigerant	Yes Exterior R600a		
Interior Light Fan Type Refrigerant Refrigerant Amount	Yes Exterior R600a 0.64 oz.		
Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI	Yes Exterior R600a 0.64 oz. 180.0		
Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI Low Side PSI	Yes Exterior R600a 0.64 oz. 180.0 80.0		
Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI Low Side PSI Inter Height	Yes Exterior R600a 0.64 oz. 180.0 80.0 25.75" (65 cm)		
Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI Low Side PSI Inter Height Interior Width	Yes Exterior R600a 0.64 oz. 180.0 80.0 25.75" (65 cm) 21.0" (53 cm)		

Compressor Step Depth	5.5" (14 cm)
Temperature Range	34º to 43ºF



