

SCFM73



33.25" x 37.5" x 22.25" (H x W x D)

Commercially listed 6.7 cu.ft. manual defrost chest freezer in white with stainless steel corner guards and lock

Highlights:

Commercially approved for use in foodservice establishments

Manual defrost operation and static cooling system

Lock included for optional security

Product Features:

Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for commercial use
Lock included	Ships with a keyed lock and two keys for optional installation on the lid
Manual defrost operation	Static cooling system with a front drain for easier defrosting as needed
Counterbalanced hinges	The lid will remain open once lifted for easier loading
Thick insulation	Solid walls ensure proper insulation for reliable storage
Stainless steel front corner protectors	Factory-installed external "bumpers" to help protect the corners in busy high traffic environments
Hammered aluminum interior	Solid construction for durable storage in busy settings
Easy-grip handle	External handle for easy opening (ships unassembled)
Adjustable thermostat	Dial thermostat ensures intuitive temperature management



SCFM73 Specifications:

Overview	
Height of Cabinet	33.25" (84 cm)
Width	37.5" (95 cm)
Depth	22.25" (57 cm)
Depth with Handle	24.0" (61 cm)
Capacity	6.7 cu.ft. (190 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.4
Voltage/Frequency	115 V AC/60 Hz
Shipping Weight	86.0 lbs. (39 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101080833
Freezer	
Door Swing	Lift-Up
Interior Height	26.0" (66 cm)
Interior Width	32.0" (81 cm)
Interior Depth	15.0" (38 cm)
Thermostat Type	Dial
Refrigerant Type	R600a
Refrigerant Amount	1.76 oz.
High Side PSI	300.0
Low Side PSI	130.0
Compressor Step Height	8.75" (22 cm)
Compressor Step Width	7.75" (20 cm)
Compressor Step Depth	15.0" (38 cm)
Temperature Range	-10 to -26°C

