







For over 70 years, the name Notrax® has meant superior quality, service, and innovative products. Now this brand is a cornerstone of Justrite Safety Group, offering the widest selection of products to a variety of markets and applications including entrance mats, anti-fatigue/safety mats, and products designed specifically for use in professional food service environments. Notrax® offers a complete selection of floor matting options to meet any application requirement, quality expectation, and budget.

- Track record of manufacturing high-quality mats for over seventy years
- All products are manufactured in ISO certified facilities
- Notrax® offers anti-fatigue matting, entrance matting, safety matting, food service matting and specialty mats designed for a variety of industries



PRODUCT INFORMATION

109 - BRUSH-STEP® features a lighter-weight double rib high/low design that performs the scraping function of the mat. The ribbed surface brushes, channels, and conceals dirt and debris and is the perfect choice for light to medium traffic areas.

Material: Polypropylene carpet w/vinyl backing

Features and Benefits:

- Scraper mat
- Lighter-weight double rib high/low design that performs the scraping function of the mat (Note: ribs run length of mat)
- 18 ounces of needle-punched yarn per square yard
- Low profile to perform in narrow clearance doorways
- Vinyl backing ensures minimal buckling and mat movement



MODEL: 109

ATIONS

- Schools
- Hospital Entrances
- Lobbies
- Entranceways

SPECIFICATIONS

Stock Sizes	2'x3', 3'x4', 3'x5', 3'x6', 3'x10',4'x6', 4x8'		
roll Sizes	3'x60', 4'x60', 6'x60'		
Thickness	3/8"		
Cut Lengths	3', 4', and 6' widths (up to 60' long)		
Colors	Charcoal Green	Brown Slate Blue	Red/Black

Performance: Good Better Best Superior
Wear Retention
Crush Resistance
Soil Resistance
Function & Appearance



TESTING DATA

Test	Test Description	Results
ASTM D3884-01	Abrasion Resistance ASTM D3884-01 (Results measured in weight loss - %)	@ 1,000 cycles** (4.4%)
ASTM D6540-05	Accelerated Soiling (Based on visual inspection)	No change after vacuum & extraction
ASTM D5252-98a	Accelerated Wear (Based on visual inspection @ 4,000 cycles)	Noticeable change in appearance and color
Water Retention	(Results measured in weight gain) Gallons per sq. yd.	.25
CPSC FF 1-70 ASTM D-2859	Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	Pass

^{*}Testing performed by an independent test laboratory.

NOTRAX®

5655 West 73rd Street Chicago, IL 60638

PHONE: (800) 621-2802

FAX: (800) 322-7105

EMAIL: customerservice@notrax.com

www.notrax.com

Ver: 4/19







Justrite Safety Group is the leading source of safety equipment for flammables and hazardous materials storage and handling, asset protection, environmental protection spill containment, absorbents, specialized chemical storage, cable management, safety showers and eye/face washes, matting, and vehicle safety equipment. Learn more at Justrite.com, Checkers-safety.com, and Notrax.com.