

2-Sided Split Grill

The all new doughXpress® 2-Sided Split Grill has been engineered to handle the demands of high volume production. The simple controls make it very easy to operate. You won't find a better 2-Sided Grill than our doughXpress® grills. Available in the following options; two surface finishes (panini or flat), split or single lid construction, and 120 or 208 volt.

2-Sided Panini Grill is designed to grill sandwiches, chicken breasts, hamburgers, Reuben's, Philly steak sandwiches, Cubans, burritos, vegetables and or a variety of meat or chicken.

2-Sided Flat Grill is designed for grilling burritos, quesadillas and more.



DXP-PS1577
(Split Lid - Panini)



DXP-CS1577
(Split Lid - Flat)



DXP-CS157
(Single Lid - Flat)



DXP-PS157
(Single Lid - Panini)

FEATURES

- Digital control located on front with easy to operate functionality
- Two user adjustable timers for each side
- Spring assisted easy lift platens with two lift stops
- Self-Adjusting thickness
- Special heavy-duty lower grilling surface
- Powerful heating technology offers powerful heating capability up to 525° F
- Removable grease tray for easy cleaning
- Includes 48" cord and NEMA plug
- Two platen styles available:
Flat or Panini (grooved)

SPLIT LID

- Handle design allows for one hand operation
- 15" x 15" lower heating surface size with split upper surface

SINGLE LID

- All the same great features as the Split Lid design but utilizing half the counter space.
- 15" x 7" lower heating surface size

FEATURES

- NEW easy-to-operate color LCD touch screen controller with built in programmable timer, temperature control and resettable counter
- All stainless metal housing
- Large opening clamshell design
- Aluminum upper and lower platens
- Sleek, modern, durable, easy to clean design
- Two model sizes available:
Split Lid & Single Lid
- Two platen styles available:
Flat or Panini (grooved)

CERTIFICATIONS

- ETL Electrical Safety
- ETL Sanitation

ACCESSORIES (Not Included)

- DXC-3 cart (one lower shelf)
- TXC-3 cart (with 6 rack rails)
- Release agent
- DX Scraper - Grooved

TEMPERATURE RANGE

- Off - 525°F (273°C)



DIMENSIONS:

Model	W	H		D	LBS
		(Closed)	(Open)		
DXP-PS-1577	18 13/16	10 3/8	29	23	93
DXP-CS-1577	18 13/16	10 3/8	29	23	93
DXP-PS-157	10	10 3/8	29	23	57
DXP-CS-157	10	10 3/8	29	23	57

SHIPPING DIMENSIONS:

Model	W	H	D	LBS
DXP-PS-1577	27	13	37	116
DXP-CS-1577	27	13	37	116
DXP-PS-157	TBA			
DXP-CS-157	TBA			

DXP-PS-1577

Split Lid - Panini

ELECTRICAL

120 Volt / 60 Hz
2100 Watts / 17.0 Amps
5-30P NEMA Plug

Also available in 208 Volt. Call for details.

DXP-PS-157

Single Lid - Panini

ELECTRICAL

120 Volt / 60 Hz
1225 Watts / 10.2 Amps
5-15P NEMA Plug

Also available in 208 Volt. Call for details.

DXP-CS-1577

Split Lid - Flat

ELECTRICAL

120 Volt / 60 Hz
2100 Watts / 17.0 Amps
5-30P NEMA Plug

Also available in 208 Volt. Call for details.

DXP-CS-157

Single Lid - Flat

ELECTRICAL

120 Volt / 60 Hz
1225 Watts / 10.2 Amps
5-15P NEMA Plug

Also available in 208 Volt. Call for details.

HIX® Corporation recommends all equipment is installed with surge protection & in a climate controlled environment for best results.

doughXpress.

HIX® CORPORATION COMMERCIAL FOOD DIVISION

Product improvement may require specifications to change without notice



doughxpress.com

800-835-0606

1201 E. 27th Terrace
Pittsburg, KS 66762
USA

